



## ASW366

**Sirena con flash para montar en pared. Base de perfil bajo. Roja con lente roja.**

### General

---

The ASW366 is a RED, general purpose, wall mount, electronic sounder and beacon for fire alarm applications. It features a special base containing all wiring connections allowing for easy placement or removal of the device. With an EN54-23 approved coverage pattern of W-2.4-7.5 for the beacon, each ASW366 may be mounted up to 2.4m high and cover a square room of 7.5 x 7.5m with a single device.

### Easy and Fast Installation

---

The ASx360 series alarm sounder/beacons allow faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws these devices use TimeSaver™ bases from the 630 series detector lines. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

### Efficient and versatile

---

The ASx360 series sounders provide high sound output at a low current, thus reducing power requirements and system cost. They are supplied with a volume control as standard, allowing final audio adjustments to be made during installation. With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation.

The ASx360 series beacons utilise a specially designed lens giving a uniformed light output over the specified coverage area.

The mechanism for locking the device to the base may be activated if required. Once activated, a special tool is required to remove the sounder from the base.



### Detalles

---

- High sound output with Pulse Alert™ technology
- 32 Tones user selectable
- Automatic synchronisation
- Volume control and adjustable flash rate
- Anti-Tamper locking mechanism
- Shallow mouting base with wiring to the base
- Seperate sounder and beacon and control
- EN54:3 and EN54:23 approved, CPR Certified

# ASW366

Sirena con flash para montar en pared. Base de perfil bajo. Roja con lente roja.

## Especificaciones técnicas

### General

Compatibilidad	All conventional notification circuits
Monitorización de línea	Polarised input

### Eléctrico

Tipo de fuente de alimentación	VCC
Voltaje de funcionamiento	17 to 60 VDC
Consumo de corriente	5.1 mA (sounder) 20 mA @ 0.5 Hz (VAD)

### Sirena

Nivel de salida	85 to 97dB(A) @ 1 m (tone dependant) Continuous Operation
Tonos seleccionables	32
Sincronización	Phased start

### VAD

Color	Red
Calificación	W-2.4-7.5
Cobertura de la planta	56.25 m <sup>2</sup>
Frecuencia de destello	0.5 Hz
Sincronización	Supported

### Físico

Dimensiones físicas	100 x 100 mm (Ø x D)
Peso neto	215 g
Color	Rojo
Tipo de Montaje	Montaje sobre base, Montaje en pared
Posición de montaje	Pared
Base de montaje	Superficial
Material	Alto impacto policarbonato
Textura	Smooth

### Medioambiental

Antivandálico	No
Temperatura de funcionamiento	-25 to +70°C
Humedad relativa	5 to 95% noncondensing
Entorno	Interior
Clasificación IP	IP21

### Regulador

Cumplimiento	CE, REACH, RoHS 3, WEEE
Certificación	CPR
Normativas	EN54-3; EN54-23

EN54-23 Coverage: W-2.4-7.5

