

2MP Fixed-focal Wi-Fi Turret Network Camera





Series Overview

The Turret Series, which is under the Dahua Wireless series, are cameras that are not only easy to install and operate, but also perform outstandingly and are cost-effective. They capture sharp, detailed images of scenes in high definition and offer powerful functions, such as AI human detection, to accurately trigger alarms. Information is also synchronously sent to your phone to keep you up-to-date. With its IP67 rating, these cameras are able to withstand harsh environments, making them highly suitable for use in small and medium-sized settings such as small-sized retail stores.



Low-cost storage



Easy to use

Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.







Specifications

Camera

| Camera | | Image Rotation | 0°/180° |
|---------------------------------|--|-----------------------|--|
| Image Sensor | 1/3" CMOS | Built-in MIC | Yes, built-in Mic |
| Max. Resolution | 1920 (H) × 1080 (V) | Audio Compression | G.711a; G.711Mu; PCM; G.726 |
| Electronic Shutter Speed | Auto/Manual 1/3 s–1/100,000 s | Network | |
| Illumination Distance | Up to 30 m (98.53 ft) | Network Port | RJ-45 (10/100 Base-T) |
| Illuminator On/Off Control | Auto | Wi-Fi | IEEE802.11b/g/n 2.4–2.4835 GHz; 2.4 G |
| Illuminator Number | 2 (Warm light) | Storage | Micro SD card (support max. 256 GB) |
| Max. Aperture | F1.6 | Management Software | Smart PSS; DSS; DMSS |
| Field of View | 2.8 mm: H: 98°; V: 55°; D: 115° 3.6 mm: H: 78°; V: 41°; D: 94° | Mobile Client | iOS;Android |
| | | General | |
| Intelligence Human Detection | Support the classification and accurate detection of human | Certifications | CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; CE-RED: Radio Equipment Directive 2014/53/EU |
| Video & Audio | | Power Supply | 12 VDC |
| Video Compression | H.264B; H.264; H.264H; H.265 Main stream: 1920 × 1080@(1–25/30 fps) | Power Consumption | Basic: 2 W (12 VDC) Max. (H.265+warm light intensity): 5.8 W (12 VDC) |
| Video Frame Rate | Sub stream: 640 × 480@(1-25/30 fps) ' ' *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity. | Operating Temperature | -40 °C to +60 °C (-40 °F to +140 °F) |
| | | Operating Humidity | ≤95% |
| Resolution | 1080p (1920 ×1080); 1280 × 960 (1280 × 960); 1280 | Protection | IP67 |
| Video Bit Rate | × 720 (1280 × 720) H.264: 32kbps ~ 4096kbps H.265: 12kbps ~ 4096kbps | Casing Material | Inner core: Metal + Plastic Cover: Plastic |
| Day/Night | Color/B/W | Product Dimensions | Φ109.9 mm × 102.2 mm (Φ4.33" × 4.02") |
| Motion Detection | OFF/ON | Net Weight | 323 g (0.71 lb) |
| Smart Illumination | Yes | | |
| Smart IIIumination | 103 | | |

What's in the box



Tools:

Installation Position Map×1 Mounting Plate×1 Screw Package×1 Waterproof Connector x 1

Documents:

QR Code×1 Quick Start Guide×1 Legal and Regulation Information×1

Power: Power Adapter×1