

KE-DBA-AUXW

Intelligent addressable base accessory - deep base (white)

General

The innovative Excellence range of intelligent addressable devices offers advanced features for reliability and peace of mind. Coupled with features for ease of installation and maintenance on new fire detection systems, it's a perfect match for exceptional overall performance.

The KE-DBA-AUXW is an Excellence series, surface mount base accessory. It allows cabling to be installed by running standard electrical conduit directly into the base, leaving no exposed cabling.

Preparation


The standard rear cable entry into the base is available with the same wide opening dimensions as the standard base with ample room for cables. In addition, four entry points are provided on the wall of the fixture to accommodate side entry, spaced at 90° around the base to allow entry and exit in all directions.

Installation

The conduit entry points are conveniently supplied with breakouts and drill locations to facilitate either installation method.

Keyhole screw fixing locations adds to the ease of installation, with built-in flexibility features to allow for mounting on uneven surface without distorting of the base.

The standard Excellence series detector base fits snugly inside the fixture, completing the installation with the same feature set as for standard surface mount installation, including address tag mounting ability in two locations, head locking to avoid unauthorised detector removal, and device orientation features for quick, easy and secure detector placement.



Details

- Large rear cable entry with ample space for cables
- Side conduit entry protects cables from damage
- Drill location and breakout support for conduit entry
- Support for uneven mounting surfaces with stress relief
- Installation fixture with first fix screw option reduces installation time and effort
- Dual address tag locations avoids alignment to make tags visible
- Supports standard Excellence series bases without feature loss, all base features remain usable
- Supports access to the selectable detector locking mechanism that protects against unauthorised detector removal

KE-DBA-AUXW

Intelligent addressable base accessory - deep base (white)

Especificaciones técnicas

Geral

Compatibilidad	Excellence series bases
----------------	-------------------------

Físico

Dimensiones físicas	130 x 48 mm (Ø x D)
Peso neto	165 g
Colour	Señal blanca (RAL 9003)
Mounting type	Montaje en el techo
Cable entries	5 (1 off rear, 4 off 25 mm (Ø) Conduit)
Material (caja)	ABS moldeado

Medioambiental


Antivandálico	No
Temperatura de funcionamiento	-30 to +85°C
Relative humidity	20 to 95% noncondensing
Environment	Interior

Regulador

Cumplimiento	CE, REACH, RoHS 3, WEEE
Certificación	CE

Productos compatibles

Categoría	Referencia	Descripción
Dispositivo de detección	KE-DB3010W	Accesorio detector inteligente serie Excellence - base estándar
Dispositivo de detección	KE-DBA-TAGW	Accesorio base direccionable inteligente - Etiqueta de dirección (blanca)



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 23 February 2024 - 12:54