

## **KP-140/141 PG2** Two-way Wireless Keypad



- PowerG<sup>®</sup> two-way Frequency Hopping Spread Spectrum FHSS-TDMA technology provides robustness and reliability closer than ever to wired
- Ideal for arming, disarming, emergency signaling, home automation and remote control applications
- Typical indoor range: 50-100m
- Indicates entry and exit periods even when not touched by a user
- Audible exit warning
- Visual indications for system status, troubles and memory
- Wall-mount bracket
- Battery life 4-5 years with typical use
- Proximity reader (KP-141 only) can be used even with panels that do not have a built-in proximity reader

KP-140/141 PG2 is a portable, wireless, two-way keypad for PowerMaster<sup>®</sup> systems. It enables easy arming and disarming of the alarm system and initiation of emergency, fire and panic alarms. It also controls programmable outputs (PGM) and X-10 devices from anywhere in the home or office. Two-way communication with the control panel provides homeowners with visual indication of successful command execution and system status.

## **Specifications:**

Battery type: Weight

(including battery):

3V, CR123A Lithium Battery 107g (3.4oz)

Operating temperature:

Operating environment:

Dimensions:

(32°F to 120°F).

0°C to 49°C

Indoor

127 x 70 x2 4mm (5 x 2.75 x 1in)

## Certifications:

Sister of their owners. Visonic reserves the right to change information or specifications without notice.