

# LM22-L200

## 21.5" FHD Monitor



#### Features:

- $\cdot$  Industrial level LCD panel, suitable for continuous 24/7 operation
- · High fidelity digital processing for a brilliant and vivid video
- · 5ms response time for no motion blur, judder or ghosting
- · Included desk stand is easily removable for standard VESA mounting
- · Support HDCVI/HDTVI/AHD/CVBS signal input and output
- · Built in speakers













#### **Technical Specification**

| M   | od | اما |
|-----|----|-----|
| IVI | ΟU | ıeı |

| Model                | LM22-L200       |
|----------------------|-----------------|
| Display              |                 |
| Screen Size          | 21.5"           |
| Aspect Ratio         | 16:9            |
| Resolution           | 1920×1080 (FHD) |
| Backlight            | LED             |
| Brightness/Luminance | 200cd/ m²       |
| Contrast Ratio       | 1000:1          |
| Display color        | 16.7M(8bit)     |
| Viewing Angle(H/V)   | 170°(H)/160°(V) |
| Response Time        | 5ms             |
| Refresh Rate         | 60Hz            |
|                      |                 |

#### Signals

| Input  | HD×1 (support HDCVI, HDTVI, AHD, CVBS), VGA×1, HDMI×1, BNC×1, Audio×1 |      |
|--------|-----------------------------------------------------------------------|------|
| Output | HD×1 (support HDCVI, HDTVI, AHD, CVBS)                                |      |
|        | Speaker                                                               | 2W×2 |

#### General

Power Supply AC100~240V (+/-10%), 50/60 Hz

| Consumption (Standard)         | ≤30W                                  |                           |
|--------------------------------|---------------------------------------|---------------------------|
| Consumption (Standby)          | ≤0.5W                                 |                           |
| Туре                           | Internal                              |                           |
| Net Weight                     | 3.8 kg (8.4lb)                        |                           |
| Gross Weight                   | 5.0kg (11.0lb)                        |                           |
| Bezel Width                    | 24mm (U), 19.4mm (R/L), 25.4mm (B)    |                           |
| VESA                           | 100×100mm (3.9"×3.9")                 |                           |
| Dimension without base (W×H×D) | 516.6×316.7×51.2mm (20.3"×12.5"×2.0") |                           |
| Package(W×H×D)                 | 565×420×116mm (22.2"×16.5"×4.6")      |                           |
| Work Environment               | Temperature                           | 0°C~ 40°C                 |
|                                | Humidity                              | 10%~85%                   |
| Package(W×H×D)                 | 565×420×116mm (22.2"×<br>Temperature  | :16.5"×4.6")<br>0°C~ 40°C |

#### Accessory

| Standard       | VGA cable, power cable, pedestal |
|----------------|----------------------------------|
| Optional       | Hanging bracket                  |
| Certifications |                                  |
| Certifications | CE/FCC                           |

## Essential Security Series | LM22-L200

### **Dimensions**(mm)



