



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Telephone: +86 (0) 21 6191 5666


Fax: +86 (0) 21 6191 5678

ee.shanghai@sgs.com

Report No.: SHEM171000728301

Page: 1 of 33

TEST REPORT

Application No.: SHEM1710007283IT
Applicant: Zhejiang Dahua Vision Technology Co., Ltd.
Address of Applicant: No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China
Manufacturer: Zhejiang Dahua Vision Technology Co., Ltd.
Address of Manufacturer: No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China
Factory: 1, ZHEJIANG DAHUA VISION TECHNOLOGY CO., LTD.
2, ZHEJIANG DAHUA ZHILIAN CO., LTD.
Address of Factory: 1, No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China
2, No.28, Dongqiao Road, Dongzhou Street, Fuyang District, Hangzhou, P.R.China.
Equipment Under Test (EUT):
EUT Name: PTZ12 IR POSITIONING SYSTEM
Model No.: DH-PTZ12248V-IRB-N, DH-PTZ12xyzutv-IRa-N, PTZ12xyzutv-IRa-N
("x" can be 1-9 or blank; "y" can be 0-9 or blank; "z" can be 0-9 or blank;
"u" can be A-Z or blank; "t" can be A-Z or blank or missing; "v" can be N or P
or blank; "a" can be A-Z or blank)¤
¤ Please refer to section 2 of this report which indicates which model was
actually tested and which were electrically identical.
Trade mark: 
Standards: 47 CFR Part 15, Subpart B:2016
Date of Receipt: 2017-10-30
Date of Test: 2017-11-02
Date of Issue: 2017-11-27

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.





Parlam Zhan
E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record				
Version	Chapter	Date	Modifier	Remark
00	/	2017-11-27	/	Original

Authorized for issue by:			
Tested By	 Bruce_tang /Project Engineer	2017-11-06 Date	
Checked By	 Zenger_zhang /Reviewer	2017-11-06 Date	



2 Test Summary

Emission Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at Mains Terminals (150kHz-30MHz)	47 CFR Part 15, Subpart B:2016	ANSI C63.4	Class A	Pass
Radiated Emissions (30MHz-1GHz)	47 CFR Part 15, Subpart B:2016	ANSI C63.4	Class A	Pass
Radiated Emissions (above 1GHz)	47 CFR Part 15, Subpart B:2016	ANSI C63.4	Class A	Pass

Internal Source	Upper Frequency
Below 1.705MHz	30MHz
1.705MHz to 108MHz	1GHz
108MHz to 500MHz	2GHz
500MHz to 1GHz	5GHz
Above 1GHz	5th harmonic of the highest frequency or 40GHz, whichever is lower

Declaration of EUT Family Grouping:

There are series models mentioned in this report and they are the similar in electrical and electronic characters. Only the model DH-PTZ12248V-IRB-N was tested since their differences are model number and appearance.



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION.....	5
4.1 DETAILS OF E.U.T.	5
4.2 DESCRIPTION OF SUPPORT UNITS.....	5
4.3 MEASUREMENT UNCERTAINTY.....	5
4.4 TEST LOCATION	6
4.5 TEST FACILITY	6
4.6 DEVIATION FROM STANDARDS.....	6
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
5 EQUIPMENT LIST.....	7
6 EMISSION TEST RESULTS.....	9
6.1 CONDUCTED EMISSIONS AT MAINS TERMINALS (150kHz-30MHz)	9
6.1.1 E.U.T. Operation.....	9
6.1.2 Test Setup Diagram.....	9
6.1.3 Measurement Data	9
6.2 RADIATED EMISSIONS (30MHz-1GHz)	12
6.2.1 E.U.T. Operation.....	12
6.2.2 Test Setup Diagram.....	12
6.2.3 Measurement Data	12
6.3 RADIATED EMISSIONS (ABOVE 1GHz)	15
6.3.1 E.U.T. Operation.....	15
6.3.2 Test Setup Diagram.....	15
6.3.3 Measurement Data	15
7 PHOTOGRAPHS.....	18
7.1 CONDUCTED EMISSIONS AT MAINS TERMINALS (150kHz-30MHz) TEST SETUP.....	18
7.2 RADIATED EMISSIONS (30MHz-1GHz) TEST SETUP	18
7.3 RADIATED EMISSIONS (ABOVE 1GHz) TEST SETUP	19
7.4 EUT CONSTRUCTIONAL DETAILS	20-33



4 General Information

4.1 Details of E.U.T.

Power supply: AC24V
Transformer : A24-5A-950,
AC120V 60Hz input , AC24V 5A output
Cable: signal and AC24V power cord : 1.2m

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Laptop 1	LENOVO	R400	--
7"LCD HD DVR	/	DS-8104AHQLI-E4	--

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Conducted Emission at mains port using AMN	3.2dB (9kHz to 150kHz)
		3.0dB (150kHz to 30MHz)
	Conducted Emission at mains port using VP	1.9 dB(9kHz to 30MHz)
	Conducted Emission at telecommunication port using AAN	2.4 dB(150kHz to 30MHz)
2	Radiated Power	3.5dB
3	Radiated emission	4.4dB (30MHz-1GHz)
		4.6dB (1GHz-6GHz)
4	Radiated Immunity	1.64dB
5	Conducted Immunity	0.96dB
6	ESD	6 %
7	EFT (Electrical Fast Transients)	5 %
8	Surge Immunity	5 %
9	Voltage Dips and Interruptions	4 %
10	20 system	1.5dB
11	Temperature test	1 °C
12	Humidity test	3%
13	DC power test	0.5 %



4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab
588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868,C-4336,T-2221,G-830 respectively.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Emissions at Mains Terminals (150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI test receiver	Rohde & Schwarz	ESR7	SHEM162-1	2016-12-29	2017-12-28
Line impedance stabilization network	SCHWARZBECK	NSLK8127	SHEM061-1	2017-05-17	2018-05-16
Line impedance stabilization network	EMCO	3816/2	SHEM019-1	2016-12-29	2017-12-28
Pulse limiter	Rohde & Schwarz	ESH3-Z2	SHEM029-1	2017-08-01	2018-07-31
Shielding Room	ZHONGYU	8*4*3M	SHEM079-2	2016-12-29	2017-12-28
CE test Cable	/	/	CE01	2016-12-29	2017-12-28

Radiated Emissions (30MHz-1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI test receiver	Rohde & Schwarz	ESU40	SHEM051-1	2017-09-26	2018-09-25
CONTROLLER	INNCO	CO200	SHEM047-1	N/A	N/A
ANTENNA MAST	INNCO	MA400-EP	SHEM047-2	N/A	N/A
TURN DEVICE	INNCO	DE 3600-RH	SHEM047-3	N/A	N/A
Broadband UHF-VHF ANTENNA	SCHWARZBECK	VULB9168	SHEM048-1	2017-02-28	2018-02-27
Semi/Fully Anechoic	ST	11*6*6M	SHEM078-2	2017-07-22	2018-07-21
Low Amplifier	CLAVIO	BDLNA-0001-412010	SHEM164-1	2017-08-22	2018-08-21

Radiated Emissions (above 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI test receiver	Rohde & Schwarz	ESU40	SHEM051-1	2017-09-26	2018-09-25
CONTROLLER	INNCO	CO200	SHEM047-1	N/A	N/A
ANTENNA MAST	INNCO	MA400-EP	SHEM047-2	N/A	N/A
TURN DEVICE	INNCO	DE 3600-RH	SHEM047-3	N/A	N/A
Double ridged broadband horn ANTENNA	SCHWARZBECK	BBHA9120D	SHEM050-1	2017-01-14	2018-01-13
High-amplifier	SCHWARZBECK	SCU-F0118-G40-BZ4-CS	SHEM050-2	2017-01-14	2018-01-13
Semi/Fully Anechoic	ST	11*6*6M	SHEM078-2	2017-07-22	2018-07-21



General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Digital pressure meter	YONGZHI	DYM3-01	SHEM082-1	2017-03-03	2018-03-02
Temperature&humidity recorder	ShangHai weather meter work	ZJ 1-2B	SHEM042-1~6	2017-09-13	2018-09-12
Digital Multimeter	FLUKE	17B	SHEM043-5	2017-09-13	2018-09-12
Autoformer regulator	Guangzhou bao de	TDGC2-5KVA	SHEM150-1	N/A	N/A
Multi-purpose tong tester	FLUKE	316	SHEM001-1	2017-01-29	2018-01-28

6 Emission Test Results

6.1 Conducted Emissions at Mains Terminals (150kHz-30MHz)


Test Requirement:	47 CFR Part 15, Subpart B:2016
Test Method:	ANSI C63.4
Frequency Range:	150kHz to 30MHz
Limit:	
0.15M-0.5MHz	79dB(μV) quasi-peak, 66dB(μV) average
0.5M-30MHz	73dB(μV) quasi-peak, 60dB(μV) average
Detector:	Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz

6.1.1 E.U.T. Operation

Operating Environment:

Temperature:	23.2 °C	Humidity:	51.5 % RH	Atmospheric Pressure:	1020 mbar
Test mode	a: Normal Working_connect audio in , audio out , alarm in , alarm out , RS485 , video ports to DVR , and connect ethernet port to laptop , keep DVR and laptop viewing video with PTZ full scanning continual .				

6.1.2 Test Setup Diagram




6.1.3 Measurement Data

An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected.



Mode:a; Line:Live Line




Site : chamber
Condition : LISN-L-2017
Project No: 7283IT
Test mode : a

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.202	10.83	0.11	9.81	20.75	53.54	-32.79	Average
2	0.202	17.79	0.11	9.81	27.71	63.54	-35.83	QP
3	1.005	13.05	0.11	9.84	23.00	46.00	-23.00	Average
4	1.005	21.83	0.11	9.84	31.78	56.00	-24.22	QP
5	1.203	8.04	0.11	9.84	17.99	46.00	-28.01	Average
6	1.203	17.06	0.11	9.84	27.01	56.00	-28.99	QP
7	2.309	-1.02	0.12	9.85	8.95	46.00	-37.05	Average
8	2.309	18.56	0.12	9.85	28.53	56.00	-27.47	QP
9	4.430	13.33	0.11	9.86	23.30	46.00	-22.70	Average
10	4.430	25.48	0.11	9.86	35.45	56.00	-20.55	QP
11	17.755	16.86	0.17	10.03	27.06	50.00	-22.94	Average
12	17.755	21.55	0.17	10.03	31.75	60.00	-28.25	QP



Mode:a; Line:Neutral Line



Site : chamber
Condition : LISN-N-2017
Project No: 7283IT
Test mode : a

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.202	10.44	0.12	9.81	20.37	53.54	-33.17	Average
2	0.202	18.06	0.12	9.81	27.99	63.54	-35.55	QP
3	1.005	12.27	0.11	9.84	22.22	46.00	-23.78	Average
4	1.005	21.14	0.11	9.84	31.09	56.00	-24.91	QP
5	1.888	5.35	0.12	9.85	15.32	46.00	-30.68	Average
6	1.888	14.35	0.12	9.85	24.32	56.00	-31.68	QP
7	2.285	-0.64	0.13	9.85	9.34	46.00	-36.66	Average
8	2.285	18.11	0.13	9.85	28.09	56.00	-27.91	QP
9	4.361	8.15	0.13	9.86	18.14	46.00	-27.86	Average
10	4.361	17.30	0.13	9.86	27.29	56.00	-28.71	QP
11	17.291	19.61	0.18	10.03	29.82	50.00	-20.18	Average
12	17.291	25.66	0.18	10.03	35.87	60.00	-24.13	QP

6.2 Radiated Emissions (30MHz-1GHz)

Test Requirement:	47 CFR Part 15, Subpart B:2016
Test Method:	ANSI C63.4
Frequency Range:	30MHz to 1GHz
Measurement Distance:	3m
Limit:	
30MHz -88MHz	49.5(dBμV/m) quasi-peak
88MHz-216MHz	54.0(dBμV/m) quasi-peak
216MHz-960MHz	56.9(dBμV/m) quasi-peak
960MHz-1000MHz	60.0(dBμV/m) quasi-peak
Detector:	Peak for pre-scan (120kHz resolution bandwidth) 30M to1000MHz


6.2.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 °C Humidity: 55 % RH Atmospheric Pressure: 1020 mbar

Test mode a: Normal Working_connect audio in , audio out , alarm in , alarm out , RS485 , video ports to DVR , and connect ethernet port to laptop , keep DVR and laptop viewing video with PTZ full scanning continual .

6.2.2 Test Setup Diagram




6.2.3 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.



Mode:a; Polarization:Horizontal




Condition : HORIZONTAL
EUT/Project: 7283IT
Test Mode : a

		ReadAntenna		Cable Preamp			Limit	Over	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 q	85.60	76.19	8.06	0.40	42.68	41.97	49.50	-7.53	QP
2	95.43	73.47	8.89	0.44	42.69	40.11	54.00	-13.89	QP
3	191.75	67.19	10.12	0.68	42.54	35.45	54.00	-18.55	QP
4	223.73	68.83	10.45	0.73	42.49	37.52	56.90	-19.38	QP
5	576.64	51.31	18.93	1.33	42.18	29.39	56.90	-27.51	QP
6	866.09	53.00	22.44	2.31	42.15	35.60	56.90	-21.30	QP



Mode:a; Polarization:Vertical



Condition : VERTICAL
EUT/Project: 7283IT
Test Mode : a

		ReadAntenna		Cable Preamp			Limit	Over	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 q	86.50	75.49	8.07	0.40	42.68	41.28	49.50	-8.22	QP
2	96.77	73.79	9.08	0.44	42.69	40.62	54.00	-13.38	QP
3	163.76	68.42	12.52	0.64	42.58	39.00	54.00	-15.00	QP
4	223.73	67.82	10.45	0.73	42.49	36.51	56.90	-20.39	QP
5	721.73	54.13	20.60	1.75	42.48	34.00	56.90	-22.90	QP
6	866.09	50.33	22.44	2.31	42.15	32.93	56.90	-23.97	QP

6.3 Radiated Emissions (above 1GHz)

Test Requirement:	47 CFR Part 15, Subpart B:2016
Test Method:	ANSI C63.4
Frequency Range:	Above 1GHz
Measurement Distance:	3m
Limit:	
Above 1GHz	80(dBμV/m) peak, 60(dBμV/m) average
Detector:	Peak for pre-scan (1000kHz resolution bandwidth) 1000M to 18000MHz


6.3.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 °C Humidity: 55 % RH Atmospheric Pressure: 1020 mbar

Test mode a: Normal Working, connect audio in, audio out, alarm in, alarm out, RS485, video ports to DVR, and connect ethernet port to laptop, keep DVR and laptop viewing video with PTZ full scanning continual.

6.3.2 Test Setup Diagram




6.3.3 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.



Mode:a; Polarization:Horizontal




Condition : HORIZONTAL
EUT/Project: 7283IT
Test mode : a

		ReadAntenna		Cable Preamp			Limit	Over	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	9613.43	37.69	38.59	9.62	42.30	43.60	59.50	-15.90	Average
2	9613.43	47.56	38.59	9.62	42.30	53.47	79.50	-26.03	Peak
3	11433.91	36.58	40.24	9.76	41.76	44.82	59.50	-14.68	Average
4	11433.91	46.74	40.24	9.76	41.76	54.98	79.50	-24.52	Peak
5	13326.75	39.94	39.85	10.18	42.00	47.97	59.50	-11.53	Average
6	13326.75	49.54	39.85	10.18	42.00	57.57	79.50	-21.93	Peak
7	14618.17	36.54	41.75	10.24	41.35	47.18	59.50	-12.32	Average
8	14618.17	46.93	41.75	10.24	41.35	57.57	79.50	-21.93	Peak
9	15668.21	40.04	38.69	10.47	41.63	47.57	59.50	-11.93	Average
10 p	15668.21	50.75	38.69	10.47	41.63	58.28	79.50	-21.22	Peak
11	16939.94	36.47	40.39	11.55	41.31	47.10	59.50	-12.40	Average
12	16939.94	46.95	40.39	11.55	41.31	57.58	79.50	-21.92	Peak



Mode:a; Polarization:Vertical



Condition : VERTICAL
EUT/Project: 7283IT
Test mode : a


		ReadAntenna		Cable Preamp			Limit	Over	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	11172.56	36.52	40.40	9.68	41.69	44.91	59.50	-14.59	Average
2	11172.56	47.79	40.40	9.68	41.69	56.18	79.50	-23.32	Peak
3	12397.74	40.29	38.63	9.96	41.96	46.92	59.50	-12.58	Average
4	12397.74	51.78	38.63	9.96	41.96	58.41	79.50	-21.09	Peak
5	14038.45	37.78	41.17	10.31	41.67	47.59	59.50	-11.91	Average
6	14038.45	48.35	41.17	10.31	41.67	58.16	79.50	-21.34	Peak
7	15046.85	37.96	41.11	10.18	41.39	47.86	59.50	-11.64	Average
8 p	15046.85	48.65	41.11	10.18	41.39	58.55	79.50	-20.95	Peak
9	16127.69	40.26	37.99	10.79	41.51	47.53	59.50	-11.97	Average
10	16127.69	50.93	37.99	10.79	41.51	58.20	79.50	-21.30	Peak
11	17639.47	31.11	45.37	12.40	41.44	47.44	59.50	-12.06	Average
12	17639.47	42.03	45.37	12.40	41.44	58.36	79.50	-21.14	Peak

7 Photographs


7.1 Conducted Emissions at Mains Terminals (150kHz-30MHz) Test Setup



7.2 Radiated Emissions (30MHz-1GHz) Test Setup



7.3 Radiated Emissions (above 1GHz) Test Setup




7.4 EUT Constructional Details









































--End of the Report--