



# CSGE28S-24P-370W

Switch PoE 24 puertos(4PoE++) Gigabit +2RJ45+2Combo 370W  
Gestionable



## Características

- Switch Lite Managed Gigabit PoE de 28 puertos: 24 puertos PoE (4 PoE++ y 20 PoE+), 2 puertos Uplink RJ45 y 2 puertos Uplink Gigabit Combo (RJ45/SFP).
- Soporta estándar IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt.
- Cumple con IEEE 802.3, IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z.
- Gestión Lite: Soporta VLAN y gestión PoE mediante interfaz Web (IP por defecto: 192.168.1.1).
- Puertos 1-4: 4xRJ45 10/100/1000Mbps (PoE++ ≤90W).
- Puertos 5-24: 20xRJ45 10/100/1000Mbps (PoE+ ≤30W).
- Puertos 25-26: 2xRJ45 10/100/1000Mbps (Uplink).
- Puertos 27-28: 2xGigabit Combo (RJ45/SFP).
- Potencia: Total ≤370W (Fuente integrada).
- Temperatura de trabajo: -10°C ~ +50°C.
- Dimensiones: 440x200x44mm.

\*Cable de alimentación incluido.

<https://www.ibdglobal.com/shop/product/csge28s-24p-370w-switch-poe-24-puertos-4poe-gigabit-2rj45-2combo-370w-gestionable-21972>