



ASC366

Sirena con flash para montar en techo. Base de perfil bajo. Roja con lente roja.

General

The ASC366 is a RED, general purpose, ceiling mount, electronic sounder and beacon for fire alarm applications. It features a special base containing all wiring connections allowing for easy placement or removal of the device. With an EN54-23 approved coverage pattern of C-3-8.9 for the beacon, each ASC366 may be mounted up to 3m high and provide a 8.9m cylinder diameter coverage. A room size of 6.3 x 6.3m square room may therefore be covered with a single device.

Easy and Fast Installation

The ASx360 series alarm sounder/beacons allow faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws these devices use TimeSaver™ bases from the 630 series detector lines. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

Efficient and versatile

The ASx360 series sounders provide high sound output at a low current, thus reducing power requirements and system cost. They are supplied with a volume control as standard, allowing final audio adjustments to be made during installation. With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation.

The ASx360 series beacons utilise a specially designed lens giving a uniformed light output over the specified coverage area.

The mechanism for locking the device to the base may be activated if required. Once activated, a special tool is required to remove the sounder from the base.



Detalles

- High sound output with Pulse Alert™ technology
- 32 Tones user selectable
- Automatic synchronisation
- Volume control and adjustable flash rate
- Anti-Tamper locking mechanism
- Shallow mouting base with wiring to the base
- Seperate sounder and beacon and control
- EN54:3 and EN54:23 approved, CPR Certified

ASC366

Sirena con flash para montar en techo. Base de perfil bajo. Roja con lente roja.

Especificaciones técnicas

General

Monitorización de línea	Polarised input
-------------------------	-----------------

Eléctrico

Voltaje de funcionamiento	17 to 60 VDC
Consumo de corriente	5.1 mA (Sounder) 20 mA @ 0.5 Hz, 40 mA @ 1 Hz (Beacon)

Sirena

Nivel de salida	85 to 97 dB(A) @ 1 m (tone dependant) Continuous operation
Tonos seleccionables	32
Sincronización	Automatic, Phased start

VAD

Color	Red
Cobertura de la planta	up to 8.9 m diameter

Físico

Dimensiones físicas	100 x 94 (Ø x D)
Peso neto	215 g
Color	Rojo
Tipo de Montaje	Montaje en el techo
Altura de montaje	up to 3 m
Material	Alto impacto policarbonato

Medioambiental

Temperatura de funcionamiento	-25 to +70°C
Humedad relativa	5 to 95% noncondensing
Entorno	Interior
Clasificación IP	IP21

Regulador

Certificación	EN54-23, EN54-3
---------------	-----------------

EN54-23 rating

Light coverage	C-3-8.9
----------------	---------

Productos compatibles

Categoría	Referencia	Descripción
Dispositivo de notificación	ASC366W	Sirena con flash para montar en techo. Base de perfil bajo. Blanca con lente roja.
Dispositivo de notificación	ASC367	Sirena con flash para montar en techo. Base alta. Roja con lente roja.

EN54-23 Coverage: C–3-8.9

