

# VTH5221E(W)-H

IP Indoor Monitor





Technical Specification		
Model	VTH5221E(W)-H	
System		
Main Processor	Embedded Micro Processor	
Operation System	Embedded LINUX OS	
Video		
Video Compression	H.264	
Audio		
Audio Compression	G.711	
Audio Input	All-direction Microphone	
Audio Output	Built-in Loudspeaker	
Bidirectional Talk	Support Dual-way Bidirectional talk	
Display		
LCD Screen	7" 1024x600, Capacitive	
Operation Mode		
Input	Touch screen	
Interface		
Alarm In	6	
Alarm Out	1	
RS485	1	
Network		
Ethernet	10M/100Mbps Self-adaptive	
Network Protocol	TCP/IP	
General		
Memory Slot	Micro SD, Max 32GB	

#### Features

- 7" TFT Capacitive touch screen, 1024x600
- · IPC surveillance
- · Alarm integration
- $\cdot$  Micro SD card optional, max 32GB
- · Record & Snapshot(SD card needed)



















_		-
	$\Box$	

Installation	Surface & Desktop
Power	DC 12V, PoE(802.3af)
Power Consumption	Standby ≤3.5W, Work ≤5W
Working Temperature	-10°C~+55°C
Relative Humidity	10%~90%RH
Dimensions	236mm×165.5mm×43.2mm
Weight	0.9Kg

### **Dimensions**

### View Area





## Application

