

Datasheet

I180SR - 180kg External Surface Monitored Magnetic Lock

Product Description

The I180SR is an external surface monitored maglock with a holding force of up to 180kg. It is part of the range of external electromagnetic locks from CDVI offering high performance flexible locking solutions in the harshest environments.

Cased in high grade stainless steel and with a unique cover plate, all models are supplied with full fixing kits.

If a bracket is required for the installation, the 180-ZL is recommended. This Z&L bracket is designed for use with the I180SR.



DEEE

RoHS Certification

IP68

IK10



100kg pre-load (FR regulation NFS 61-937)

-40°C to 60°C

(pictures, drawings, features, dimensions, specifications), could be perceptibly different and can be changed notice. Published: 06 December 2022. CDVI_I180SR_DS_02_EN_A4_C the information contained within this docur without

Key Features

- External surface mount maglock
- Monitored
- Up to 180kg holding force
- Robust stainless steel construction
- Built-in varistor
- Ideal for external use and harsh environments





Product Specifications

Material:	High grade stainless steel
Mounting:	Surface, face or cross mounting holes
Lock mode:	Fail safe
Holding force:	180kg
Relays:	1
Contacts:	NO/NC
Weight:	0.78kg
Dimensions:	
 Maglock: 	175 x 32.5 x 22mm
Armature plate:	130 x 32 x 9mm

Electrical Specifications

Power input:	12/24Vdc
Consumption:	450mA @ 12Vdc
	225mA @ 24Vdc

Accessories



180-ZL Z&L bracket for 180kg surface magnetic locks

Unit B1 Knaves Beech Business Centre,

Davies Way, Loudwater, High Wycombe HP10 9QR



