IUI-SIR-ID Indoor Siren

www.boschsecurity.com





- ► Tamper proof 1,5mm thick steel housing
- ▶ Regulation of charging voltage to 13,8 VDC
- ▶ Noise level of 117 dBA

Functions

The IUI-SIR-OD is a self powered siren for indoor security applications producing a rated power of 117 dBA.

This siren is tampered when opening the cover and when removing the base from the wall.

The siren has the possibility of a built -in power back up, using a 12 V DC rechargeable battery, as to maintain a constant service in case of a failure of the main power supply.

In alarm only the internal battery is required. This effectively protects the charger of the panel when several sirens are powered by it.

Certifications and approvals

Certifications AFNOR (NF C 48-265, NF324-H58), INCERT (B-712-0001)

Region	Certification
Europe	CE
France	AFNOR

Installation/configuration notes

Alarm not triggered on power-up so long as the blocking signal has not appeared.

Type Qty. Component IUI-SIR-ID 1 siren

Technical specifications		
Supply voltage on +12V Charge	12 - 14,5 VDC	
Output voltage on +BAT	13,8 VDC (+/- 0,2 VDC)	
Residual ripple allowed	250 mV	
Charging current	Limited to 100mA	
Consumption without alarm on battery	5 mA	
Consumption with alarm on battery	1,6 A	
Autonomy on internal battery	no alarm triggered: 36 hours alarm triggered: 30 minutes	

Length of alarm	31 minutes
Autonomy on internal battery	72 hours
Siren blocking voltage	9 - 16 VDC (0,1mA)
Trigger voltage	Less than 4 VDC
Reset voltage	More than 9 VDC
Back up power supply	12 VDC / 2 Ah
Output Power	117 dBA at 1m
Applications	Siren for indoor applications
Temperature range	-10°C - +55°C
Degree of protection	IP31 IK08
Environment	Class II, general indoor
Dimensions	192 x 182 x 62 mm
Weight	without internal battery 2kg with internal battery 2,8kg
Type of backup batteries	12 V 2,1Ah Yuasa NP2.1-12FR 12V 2,1Ah Yucell Y2.1-12FR 12V 2,1Ah Powersonic PS 1220 V0 12V 2,2Ah Eleckson BEL120022 12V 2,3Ah ACD ST20 12V 2,1Ah Sunlight SP 12-2.1V0

Ordering information

IUI-SIR-ID Indoor Siren

IUI-SIR-ID is a self powered siren for indoor security applications producing a rated power of 117 dBA. Order number IUI-SIR-ID

Represented by:

Americas: Americas: Bosch Security Systems, Inc. 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 security.sales@us.bosch.com www.boschsecurity.us

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002 5617 BA Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

Asia-Pacific: Robert Bosch (SEA) Pte Ltd, Security Systems 11 Bishan Street 21 Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd. 201 Building, No. 333 Fuquan Road North IBP North IBP Changning District, Shanghai 200335 China Phone +86 21 22181111 Fax: +86 21 22182398 www.boschsecurity.com.cn

America Latina:

America Latina:
Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com www.boschsecurity.com