



SDS0086UK

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH) & 2015/830

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1	Product identifier	
	Product Name	Solo Smoke Detector Tester.
	Trade Name	Solo A5-XXX (XXX denotes customer variant).
	CAS No.	Mixture.
	EINECS No.	Mixture.
4.0	REACH Registration No.	None assigned.
1.2	Relevant identified uses of the substance or	
	mixture and uses advised against Identified use(s)	Smoke simulation.
	Uses advised against	None known.
1.3	Details of the supplier of the Safety Data Sheet	None known.
	Company Identification	Detectortesters (No Climb Products Ltd)
		Edison House
		163 Dixons Hill Road
		Welham Green
		Hertfordshire. AL9 7JE.
		United Kingdom
	Telephone	+44 (0) 1707 282760
	Fax	+44 (0) 1707 282777
	E-mail	SDS@detectortesters.com
1.4	Emergency telephone number	
	Emergency Phone No.	+44 (0) 1707 282760
2.	SECTION 2: HAZARDS IDENTIFICATION	
∠ . ,	SECTION 2. HAZARDS IDENTIFICATION	
2. 2.1	Classification of the substance or mixture	
		Aerosol 1; Extremely flammable aerosol.
	Classification of the substance or mixture	Aerosol 1; Extremely flammable aerosol. Pressurised container: May burst if heated.
2.1	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP)	Pressurised container: May burst if heated.
	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP) Label elements	
2.1	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP)	Pressurised container: May burst if heated.
2.1	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP) Label elements	Pressurised container: May burst if heated.
2.1	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP) Label elements	Pressurised container: May burst if heated.
2.1	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP) Label elements	Pressurised container: May burst if heated.
2.1	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP) Label elements	Pressurised container: May burst if heated. According to Regulation (EC) No. 1272/2008 (CLP)
2.1	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP) Label elements Hazard Pictogram(s)	Pressurised container: May burst if heated. According to Regulation (EC) No. 1272/2008 (CLP)
2.1	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP) Label elements Hazard Pictogram(s) Signal Word(s)	Pressurised container: May burst if heated. According to Regulation (EC) No. 1272/2008 (CLP) GHS02 Danger.
2.1	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP) Label elements Hazard Pictogram(s)	Pressurised container: May burst if heated. According to Regulation (EC) No. 1272/2008 (CLP) GHS02 Danger. H222: Extremely flammable aerosol.
2.1	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP) Label elements Hazard Pictogram(s) Signal Word(s)	Pressurised container: May burst if heated. According to Regulation (EC) No. 1272/2008 (CLP) GHS02 Danger.
2.1	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP) Label elements Hazard Pictogram(s) Signal Word(s) Hazard Statement(s)	Pressurised container: May burst if heated. According to Regulation (EC) No. 1272/2008 (CLP) GHS02 Danger. H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
2.1	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP) Label elements Hazard Pictogram(s) Signal Word(s) Hazard Statement(s)	Pressurised container: May burst if heated. According to Regulation (EC) No. 1272/2008 (CLP) GHS02 Danger. H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated. P210: Keep away from heat, hot surfaces, sparks, open
2.1	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP) Label elements Hazard Pictogram(s) Signal Word(s) Hazard Statement(s)	Pressurised container: May burst if heated. According to Regulation (EC) No. 1272/2008 (CLP) GHS02 Danger. H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source.
2.1	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP) Label elements Hazard Pictogram(s) Signal Word(s) Hazard Statement(s)	Pressurised container: May burst if heated. According to Regulation (EC) No. 1272/2008 (CLP)
2.1	Classification of the substance or mixture Regulation (EC) No. 1272/2008 (CLP) Label elements Hazard Pictogram(s) Signal Word(s) Hazard Statement(s)	Pressurised container: May burst if heated. According to Regulation (EC) No. 1272/2008 (CLP) GHS02 Danger. H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source.

2.3 Other hazards

None.



3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Product as supplied: Aerosol.

3.1 Mixtures

EC Classification No. 1272/2008

Hazardous ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard Pictogram(s) and Hazard Statement(s)
Butane	50 - 100	106-97-8	203-448-7	01-2119474691-32	GHS02, Flam. Gas 1; H220, GHS04, Press. Gas: Liquefied gas; H280
Propane	10 - 25	74-98-6	200-827-9	01-2119486944-21	GHS02, Flam. Gas 1; H220, GHS04, Press. Gas: Liquefied gas; H280
Ethanol	0 - 5	64-17-5	200-578-6	None assigned	GHS02, Flam. Liq. 2; H225

3.2 Additional Information

For full text of H/P statements see section 16.

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures Inhalation

Skin Contact Eye Contact

Ingestion

- 4.2 Most important symptoms and effects, both acute and delayed
- 4.3 Indication of any immediate medical attention and special treatment needed

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Wash skin with soap and water. Flush eyes with water for at least 15 minutes while holding eyelids open. Unlikely route of exposure. None anticipated.

Unlikely to be required but if necessary treat symptomatically.

5. SECTION 5: FIRE-FIGHTING MEASURES

Pressurised container: May burst if heated.

5.1	Extinguishing Media	
	Suitable Extinguishing Media	Extinguish with carbon dioxide, dry chemical, foam or waterspray.
	Unsuitable Extinguishing Media	Do not use water jet.
5.2	Special hazards arising from the substance or mixture	Heating may cause pressure rise with risk of bursting.
5.3	Advice for fire-fighters	Fire fighters should wear complete protective clothing including self-contained breathing apparatus. If it is safe to do so, containers should be removed from fire area because they are likely to rupture under fire conditions.



6. SECTION 6: ACCIDENTAL RELEASE MEASURES

The product is an aerosol. It is unlikely to present spillage or leakage hazard. In case of rupture, released content should be contained as any other solvent spill.

6.1	Personal precautions, protective equipment and emergency procedures	Ensure adequate ventilation. Wear suitable gloves and eye/face protection.
6.2	Environmental precautions	Do not release large quantities into the surface water or into drains.
6.3	Methods and material for containment and cleaning up	Collect mechanically and dispose of according to Section 13. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a lidded container for disposal or recovery. Containers must not be punctured or destroyed by burning, even when empty.
6.4	Reference to other sections	See Also Section: 8, 13.

7. SECTION 7: HANDLING AND STORAGE

7.1	Precautions for safe handling	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Provide adequate ventilation. Do not eat, drink or smoke during work. Wash hands thoroughly after handling.
7.2	Conditions for safe storage, including any incompatibilities	Observe official regulations on storing packagings with pressurised containers.
	Storage Temperature	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C.
	Storage Life	Stable under normal conditions.
	Incompatible materials	None anticipated.
7.3	Specific end use(s)	Smoke simulation.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION 8.

8.1 **Control parameters**

Occupational Exposure Limits 8.1.1

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m ³)	Note
Butane	106-97-8	600	1450	750	1810	WEL
Ethanol	64-17-5	1000	1920	-	-	WEL

WEL: Workplace Exposure Limit (UK HSE EH40)

8.1.2 Biological limit value

- 8.1.3 PNECs and DNELs
- 8.2 Exposure controls
- Appropriate engineering controls 8.2.1
- 8.2.2 Personal protection equipment Eye/face protection



Not established.

Not established.

Provide adequate ventilation.

If eye contact is likely: Wear protective eyewear (goggles, face shield, or safety glasses).



Skin protection (Hand protection/ Other)



8.2.3 Environmental Exposure Controls

Wear suitable gloves if prolonged skin contact is likely. Gloves: Nitrile rubber, NBR.

No personal respiratory protective equipment normally required. Handling of larger amounts: In case of insufficient ventilation, wear suitable respiratory equipment. A suitable mask with filter type A (EN14387 or EN405) may be appropriate. Not applicable.

Do not release large quantities into the surface water or into drains.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties Appearance Aerosol. Colour Colourless. Odour Characteristic. Odour Threshold Not determined. Not determined. pН . Melting Point/Freezing Point Not determined. Initial boiling point and boiling range -44 °C <0 °C Flash Point Evaporation rate Not available. Flammability (solid, gas) Extremely flammable. Upper/lower flammability or explosive limits Explosive Limit Ranges: 1.5 - 10.9 Vol-% Vapour pressure 3.8 bar @ 20 °C Density 0.58 g/cm3 @ 20 °C Vapour density Not determined. Relative density Not determined. Solubility(ies) Immiscible with water. Partition coefficient: n-octanol/water Not determined. Ignition temperature 365 °C Auto-ignition temperature Product is not selfigniting. **Decomposition Temperature** Not determined. Kinematic Viscosity Not determined. Explosive properties Not explosive. Oxidising properties Not oxidising. 9.2 Other information Organic solvents - Content 98.9%

10. SECTION 10: STABILITY AND REACTIVITY

10.1	Reactivity	Stable under normal conditions.
10.2	Chemical stability	Stable under normal conditions.
10.3	Possibility of hazardous reactions	No hazardous reactions known if used for its intended purpose.
10.4	Conditions to avoid	Heat and direct sunlight.
10.5	Incompatible materials	None anticipated.
10.6	Hazardous Decomposition Product(s)	No hazardous decomposition products known.



11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects
 Acute toxicity
 Skin corrosion/irritation
 Serious eye damage/irritation
 Respiratory or skin sensitization
 Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT - single exposure
 STOT - repeated exposure
 Aspiration hazard
 11.2 Other information

Low acute toxicity. Non-irritant. Not classified. It is not a skin sensitiser. There is no evidence of mutagenic potential. No evidence of carcinogenicity. None anticipated. Not classified. Not classified. None anticipated. None.

12. SECTION 12: ECOLOGICAL INFORMATION

- 12.1 Toxicity
- 12.2 Persistence and degradability
- 12.3 Bioaccumulative potential
- 12.4 Mobility in soil
- 12.5 Results of PBT and vPvB assessment
- 12.6 Other adverse effects

Low toxicity to aquatic organisms. The product is readily biodegradable. Unlikely to persist. The product has no potential for bioaccumulation. Immiscible with water. The product is predicted to have low mobility in soil. Not classified as PBT or vPvB. None.

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Recycle only completely emptied packaging. Containers must not be punctured or destroyed by burning, even when empty. Non-emptied aerosol: Dispose of wastes in an approved waste disposal facility. Do NOT landfill. Disposal should be in accordance with local, state or national legislation.

13.2 Additional Information

14. SECTION 14: TRANSPORT INFORMATION

UN number	
ADR, IMDG, IATA	UN 1950
UN Proper Shipping Name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS
ΙΑΤΑ	AEROSOLS, Flammable
Transport hazard class(es)	
ADR	
Class / Classification	2 5F Gases.
Label	2.1
IMDG, IATA	
Class / Division	2.1
Label	2.1
Packing Group	
ADR, IMDG, IATA	None.
Environmental hazards	
Marine Pollutant	No.
Special precautions for user	Warning: Gases.
Kemler Code	-
IMDG EMS	F-D, S-U
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
	•••
	ADR, IMDG, IATA UN Proper Shipping Name ADR IMDG IATA Transport hazard class(es) ADR Class / Classification Label IMDG, IATA Class / Division Label Packing Group ADR, IMDG, IATA Environmental hazards Marine Pollutant Special precautions for user Kemler Code IMDG EMS Transport in bulk according to Annex II of





Technical Instructions (air)

VOC-CH VOC-EU Danish MAL Code 15.2 Chemical Safety Assessment
 Class
 Share in %

 NK
 50 - 100

 98.93%
 569.8g/l

 3-1
 Not available.



16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 10, 11.

LEGEND	
LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
PBT	Persistent, Bioaccumulative and Toxic
vPvB	very Persistent and very Bioaccumulative
WGK	Wassergefährdungsklasse (Germany)
VOC	Volatile Organic Compounds
MAL Code	Måleteknisk Arbejdshygiejnisk Luftbehov
	(Regulation for the labeling concerning inhalation hazards, Denmark)
ADR	Accord européen elative au transport international des marchandises dangereuses par route
	(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG	International Maritime Code for Dangerous Goods
IATA	International Air Transport Association
Press. Gas	Gases under pressure
Flam. Gas 1	Flammable gas Category 1

Hazard Statement(s)

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.

Disclaimers

The information is based on the best knowledge of No Climb Products Ltd. and its advisors and is given in good faith, but we cannot guarantee its accuracy, reliability or completeness and therefore disclaim any liability for loss or damage arising out of use of this data. Since conditions of use are outside the control of the Company and its advisors we disclaim any liability for loss or damage when the product is used for purposes other than it is intended.

Annex to the extended Safety Data Sheet (eSDS)

No information available.