



# SD1A404DB-GNY-W-PV

Domo PTZ IP 4M H265 WiFi WDR IR20m Starlight 4x IP66 IK08  
AUDIO MIC AI



## Características

- Cámara PTZ con resolución 4MP@25FPS.
- 3 Streams simultáneos hasta 20 usuarios (ancho de banda total: 64M).
- Auto 4xZoom 2.8-12mm (H: 96.9°-31.6°; V: 51.4°-17.8°; D: 116.2°-36.4°), F1.8~F2.7.
- Bit Rate:
  - H264: 96 kbps-14,848 kbps.
  - H265: 38 kbps-8,960 kbps.
- Rango Pan/Tilt:
  - Pan: 0 ~ 355°, Tilt: 5 ~ 90°.
- Velocidad PTZ:
  - Manual: 0.1° - 70°/s Pan, 0.1° - 30°/s Tilt.
  - Preset: 0.1° - 80°/s Pan, 0.1° - 40°/s Tilt.
- Wi-Fi disponible:
  - Wi-Fi Standard: IEEE802.11b;IEEE802.11g;IEEE802.11n;IEEE802.11ax
  - Wi-Fi Frequency Range: 2.4 GHz
  - Wi-Fi Transmission Rate: 229 Mbps
  - Max Transmission Power: 20 dBm@2400-2483.5 MHz
- Software de gestión: DMSS; DSS PRO.
- TVS 6000V Protección contra descargas eléctricas.
- Dimensiones y peso:  $\Phi$ 128x65.7mm / 0.5Kg.
- \* WizSense Series: Perimeter Protection, Face Detection, People Counting, SMD 3.0.

## Productos Alternativos

[SD1A204DB-GNY](#)  
[SD1A203T-GN-W](#)  
[SD1A204DB-GNY-W](#)  
[SD1A404DB-GNY](#)

## Accesorios

[PFA107](#)  
[PFA120-V2](#)  
[PFA6400S](#)  
[PFA6400SA](#)  
[PFB220C-V2](#)  
[PFB305W](#)

<https://www.ibdglobal.com/shop/product/sd1a404db-gny-w-pv-domo-ptz-ip-4m-h265-wifi-wdr-ir20m-starlight-4x-ip66-ik08-audio-mic-ai-19507>