

Certificate of constancy of performance

0832-CPR-F0156

In compliance with Regulation 305/2011/EU of the European Parliament and of the council of 9th March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

ASC2367

**Analogue Addressable Type A Sounder and Ceiling Mounted
Red Light LED Visual Alarm Device**

(For full product details and conditions of use refer to appendix)

Produced by or for

UTC Fire and Security B. V

**Kelvinstraat 7
Weert
NL-6003 DH
The Netherlands**

and produced in the manufacturing plant(s)

Texecom Ltd

**Bradwood Court, St Crispin Way
Haslingden
Lancashire
BB4 4PW
United Kingdom**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

**EN 54-23:2010 - Visual alarm devices
EN 54-3:2001 + A1:2002 + A2:2006 - Sounders**

under system 1 are applied and that

the product fulfils all the prescribed requirements set out above.

This certificate was first issued on 20 March 2014 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.



Martin McCullagh, Certification Manager
On behalf of BRE Global Limited
Date of issue: 20 March 2014
Issue number: 1

This certificate remains the property of BRE Global Ltd and is issued subject to terms and conditions.
To check the validity of this certificate, please contact us on +44 (0)1923 664100 or email enquiries@breglobal.com.

Appendix to Certificate of constancy of performance 0832-CPR- F0156

Bases:

PSO-0017 / HSG6918 – Red Deep base

Notes:

1. ASC2367 – Red Body (red lens + red light LED) Type A – use base PSO-0017 / HSG6918
2. The sounder meets the requirements of EN 54-3:2001 at the following tones:
 - 1) 970Hz continuous,
 - 2) 800Hz/970Hz @ 2Hz
 - 3) 800Hz – 970Hz @ 1Hz
 - 6) 554Hz, 0.1s/ 440Hz, 0.4s
 - 7) 500 – 1200Hz, 3.5s/ 0.5s OFF
 - 13) 1200Hz – 500Hz @ 1Hz
3. The VAD meets the requirements of EN 54-23:2010 for the following:
 - Category C-3-9
 - Flash rates 0.5Hz and 1Hz
 - Synchronization



Martin McCullagh, Certification Manager
On behalf of BRE Global Limited
Date of issue: 20 March 2014
Issue number: 1

This certificate remains the property of BRE Global Ltd and is issued subject to terms and conditions.
To check the validity of this certificate, please contact us on +44 (0)1923 664100 or email enquiries@breglobal.com.