

# DH-HAC-HUM3201B-B

2MP Starlight HDCVI Miniature Camera

# **HDCVI**



- · Starlight, 120dB true WDR, 3DNR
- · Max 30fp@1080P
- HD and SD output switchable
- · 2.8mm fixed lens
- · Audio in interface
- · DC12V











### **System Overview**

Experience full HD 1080P video with the simplicity of using existing cabling infrastructure. The starlight HDCVI Miniature Camera presents high quality image with rich details even under extreme lowlight environment and supports 120dB true WDR. It offers multi-language OSD and HD/SD switchable output. The compact design and high image performance makes the pinhole camera an ideal choice for invisible monitoring applications such as ATM.

### **Functions**

### Elaborate Design

For better adapting the applications for invisible monitoring, the pinhole camera is designed with micro-sized compact case, which minimizes the interference against on-going activities. Taking aesthetics requirements into consideration, the body of the camera is all-black.

### 4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio\*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the HCVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility.

\* Audio input is available for some models of HDCVI cameras.

### Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

### Starlight

With the adoption of high performance sensor, the camera is able to provide incomparable performance even under extreme lowlight environment. The starlight feature allows more details to be captured and accurate color to be recognized at night or in scenes with limited illumination.

### **Wide Dynamic Range**

Embedded with industry leading wide dynamic range (WDR) technology, vivid pictures are achieved even in the most intense contrast lighting conditions. True WDR (120dB) optimizes both the bright and dark areas of a scene at the same time to provide amazing usable video.

### **Multi-formats**

The camera supports multiple video formats including HDCVI, CVBS and other two common HD analog formats in the market. The four formats can be switched over through OSD menu or by PFM820(UTC controller). This feature makes the camera to be compatible with not only HCVRs but also most end users' existing HD/SD DVRs.

### Multi-language OSD

OSD menu provides multiple image adjustments and function settings to meet the requirements of different monitoring scenes. The OSD menu includes configurations such as backlight mode, day/night, white balance and privacy mask. The camera supports 11 languages for OSD menu, namely, Chinese, English, French, German, Spanish, Portuguese, Italian, Japanese, Korean, Russian and Polish.

### Protection

Supporting ±25% input voltage tolerance, this camera suits the unstable power supply conditions. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.

### **Broadcast-quality Audio**

Audio information is used as supplementary evidence in video surveillance applications. The HDCVI camera supports audio signal transmission over coaxial cable. In addition, it adopts unique audio processing and transmission technology that best restores source audio and eliminates noise, guaranteeing the quality and effectiveness of collected audio information.

Technical Specification					
Camera					
Image Sensor		1/2.8 inch CMOS			
Effective Pixels		1920 (H) × 1080 (V), 2MP			
Scanning System		Progressive			
Electronic Shutter Speed		PAL: 1/3s-1/100000s NTSC: 1/4s-1/100000s			
S/N Ratio		>65 dB			
Minimum Illumination		Color: 0.004LuxLux/F2.4 Black & White: 0.0004LuxLux/F2.4			
Lens					
Lens Type		Fixed-focal			
Mount Type		M12			
Focal Length		2.8 mm			
Max. Aperture		F2.5			
Angle of View		$130^{\circ} \times 110^{\circ} \times 59^{\circ}$ (diagonal x horizontal x vertical)			
Iris Type	Iris Type		Fixed iris		
Close Focus Distance		0.5 m (1.6 ft)			
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	41.4 m (135.8 ft)	16.6 m (54.5 ft)	8.3 m (27.2 ft)	4.1 m (13.4 ft)
	*DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation and commissioning manual/project design tool.				

\/i	Ч	Д	$\cap$
VΙ	ч	$\subset$	U

Frame Rate	CVI: PAL: 1080P@25fps, 720P@25/50fps NTSC: 1080P@30fps, 720P@30/60fps AHD: PAL: 1080P@25fps, 720P@25fps NTSC: 1080P@30fps, 720P@30fps TVI: PAL: 1080P@25fps, 720P@25ps NTSC: 1080P@30fps, 720P@30ps CVBS: PAL: 960 × 576H NTSC: 960 × 480H
Resolution	1080P (1920 × 1080); 720P (1280 × 720); 960H (704 × 576/704 × 480)
Day/Night	Auto switch by ICR
BLC	BLC/HLC/WDR
WDR	120 dB
White Balance	Auto; manual
Gain Control	Auto; manual
Noise Reduction	3D NR
Smart IR	Yes
Electronic Defog	Yes

Digital Zoom	4 ×	
Mirror	Off/On	
Privacy Masking	Off/On	
Certifications		
Certifications	CE (EN55032, EN55024, EN50130-4,EN60950-1) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)	
Port		
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port	
Audio Input	One channel, RCA sound pick-up port	
Power		
Power Supply	12V ±30% DC	
Power Consumption	Max 2.11W	
Environmental		
Operating Temperature	-30°C to +60°C (-22°F to 140°F);<95% (noncondensation)	
Storage Temperature	-30°C to +60°C (-22°F to 140°F);<95% (noncondensation)	
Protection Grade	NA	
Construction		
Casing	Metal throughout the whole casing	
Camera Dimensions	43.5 mm $\times$ 36.2 mm $\times$ 29.5 mm (1.71" $\times$ 1.43" $\times$ 1.16")	
Net Weight	0.04 kg (0.09 lb)	
Gross Weight	0.14 kg (0.31 lb)	

Ordering Information				
Туре	Part Number	Description		
2MP Camera	DH-HAC-HUM3201BP- 0280B-S2	2MP Starlight HDCVI Miniature Camera		
	DH-HAC-HUM3201BN- 0280B-S2			
	HAC-HUM3201BP-0280B-S2			
	HAC-HUM3201BN-0280B-S2			
Accessories	PFM321	12V 1A Power Adapter		
	PFM320D-015	12V 1.5A Power Adapter		
	PFM320	12V 2A Power Adapter		

### Accessories

### Optional:







PFM320 12V 2A Power Adapter



PFM320D-015 Power Adapter

# Ceiling Mount Plane Mount

## Dimensions (mm[inch])



