

MPE Evaluation According To EN62311: 2008

Applicant : Zhejiang Dahua Vision Technology Co., Ltd.
No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China

Manufacturer : Zhejiang Dahua Vision Technology Co., Ltd.
No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China

Product Name : IP CAMERA

Type/Model : DH-IPC-HDW5231RN-Z, DH-IPC-HDW5231RP-Z, IPC-HDW5231RN-Z,
IPC-HDW5231RP-Z, DH-IPC-HDW5231RP-Z-S2, DH-IPC-HDW5431RN-Z,
DH-IPC-HDW5431RP-Z, IPC-HDW5431RN-Z, IPC-HDW5431RP-Z,
DH-IPC-HDW5431RP-Z-S2, DH-IPC-HDW5830RN-Z,
DH-IPC-HDW5830RP-Z, IPC-HDW5830RN-Z, DH-IPC-HDW5830RP-Z-S2,
DH-IPC-HDW5830RP, N58BH4Z, N58BH4ZI, IPC-HDW2231RP-ZS,
IPC-HDW2231RN-ZS, DH-IPC-HDW2231RP-ZS, DH-IPC-HDW2231RN-ZS,
IPC-HDW2231RP-ZS-S2, IPC-HDW2230RP-ZS, DH-IPC-HDW2230RP-ZS,
DH-IPC-HDW2230RN-ZS, IPC-HDW2230RN-ZS, IPC-HDW2431RN-ZS,
IPC-HDW2431RP-ZS, DH-IPC-HDW2431RP-ZS,
DH-IPC-HDW2431RN-ZS, IPC-HDW2431RP-ZS-S2,
DH-IPC-HDW2531RP-ZS-27135, DH-IPC-HDW2531RN-ZS-27135,
IPC-HDW2531RP-ZS-27135, IPC-HDW2531RN-ZS-27135,
DH-IPC-HDW2531RP-ZS, DH-IPC-HDW2531RN-ZS, IPC-HDW2531RP-ZS,
IPC-HDW2531RN-ZS

Rating : 12Vdc 1A,
POE: 48Vdc 200mA

The equipment complies with the requirements according to the following standard:

EN62311: 2008: Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)

Date of issue: 2017-6-6

Prepared by:



Jacky Shu (*Project Engineer*)

Reviewed by:



Valiant Sun (*Reviewer*)

Content

1. SUMMARY OF TESTS	3
2. RF EXPOSURE LIMIT	4
3. RF EXPOSURE ASSESSMENT	5

1. Summary of tests

TEST	REFERENCE	RESULTS
Assessment	Council recommendation 1999/519/EC	Pass

Notes: NA =Not Applicable

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

2. RF Exposure Limit

Council Recommendation 1999/519/EC: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency radiation.

Reference levels for electric, magnetic and electromagnetic fields (Table 2 of 1999/519/EC)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (uT)	Equivalent plane wave power density S_{eq} (W/m ²)
0-1 Hz	-	$3,2 \times 10^4$	4×10^4	-
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	-
8-25 Hz	10 000	$4\,000/f$	$5\,000/f$	-
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	-
0,8-3 kHz	$250/f$	5	6,25	-
3-150 kHz	87	5	6,25	-
0,15-1 MHz	87	$0,73/f$	$0,92/f$	-
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	-
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

Notes:

1. f as indicated in the frequency range column.
2. For frequencies between 100 kHz and 10 GHz, S_{eq} , E^2 , H^2 , and B^2 are to be averaged over any six-minute period.
3. For frequencies exceeding 10 GHz, S_{eq} , E^2 , H^2 , and B^2 are to be averaged over any $68/f^{0.05}$ - minute period (f in GHz).
4. No E-field value is provided for frequencies < 1 Hz, which are effectively static electric fields. For most people the annoying perception of surface electric charges will not occur at field strengths less than 25 kV/m. Spark discharges causing stress or annoyance should be avoided.
5. The shading grid stands for the applied limit in this report.

3. RF Exposure Assessment

Test result: **PASS**

3.1 ASSESSMENT REQUIREMENTS

For non-radio transmitting apparatus, the compliance assessment to emissions of E or H field has to be made according to the highest internal frequency used within the apparatus under analysis or at which the apparatus operates with the following criteria:

- ☐ Highest internal frequency of the apparatus is less than 100MHz, the assessments shall be made up to 1GHz;
- ☐ Highest internal frequency of the apparatus is between 100MHz and 400MHz, the assessment shall be made up to 2GHz;
- ☐ Highest internal frequency of the apparatus is between 400MHz and 1GHz, the assessment shall be made up to 5GHz;
- ☐ Highest internal frequency of the apparatus is above 1GHz, the measurement shall be made up to 5 × the highest frequency.

3.2 ASSESSMENT RESULT

Kind of emission: ☒ unintentional radiators ☐ intentional radiators

☒ Inherently compliant: unintentional radiators (for example incandescent light bulbs and audio/visual (A/V) equipment, information technology equipment (ITE) and multimedia equipment (MME) that does not contain radio transmitters), is deemed to meet the requirements in this standard without test.

☐ Low power compliant: the equipment is deemed to meet the requirements in this standard without test for the radiated output power is lower than P_{max} (low-power exclusion level): 20mW.

☐ E-field strength Test:

TEST DATA SUMMARY			
Carrier Frequency (MHz)	Distance between Field Sensor and device (cm)	Measured E-field Strength (V/m)	Limit (V/m)
/	/	/	/