

DHI-ITC302-RF1A-(IR) 3MP Traffic Picture Capture Camera



• High performance CCD image sensor, high color reduction degree, high sensitivity

• Embedded integration component design, built-in a variety of algorithms

· Rich variety of signal, data and communication interface

 \cdot Saving 30% power consumption compared to traditional solutions

• Temperature -40°C~+80°C, Humidity 10%~90%, suitable for the rough work scene

Overview

This new camera is mainly used in roadway ANPR system and red light enforcement system, devoting to Front-end License Plate Recognition. More than 98% vehicle capture rate, up to 95% ANPR rate and its capture speed can reach 200km/h, covering at most 2 lanes!

Technical Specification

Working Environment

Technical Data		
Image Sensor	1.8 progressive CCD	
Max. Resolution	3MP, 2048 (H)×1536 (V)	
Lenses	C-Model. Automatic control (P-IRIS drive)	
Video Frame	Up to 25 fps	
Camera Speed Shutter	1/25~ 1/100000	
Day/Night	Auto ICR (with polarized lens and infrared filter)	
Lamp	White /IR light	
Video Signal Interface	1 ×CVBS port and 2 ×100/1000M Ethernet port	
Digital I/O	2 Relay output – 1 optical coupling input – 8 optical coupling input	
Extra Interface	2 ×Mini USB and 1 ×SD interface	
Speed Range	0~200km/h	
Power,Size,Environment		
Power	DC12V, Max. 15W	

Temperature -40°C~+80°C, Humidity 10%~90%

Software Features

License Plate Recognition (LPR)	Embedded	
Monitor Lane	1-2lanes	
Video Compression	H.264H, H.264M, H.264B, MJEPG	
Remote control function	Configure through WEB client	
OSD information superimposed	Information of the picture includes time and place (channel address), lane information (number,/ direction), plate information(license plate and color), vehicle information (speed, vehicle length, body color and the type of vehicle), illegal (illegal event name and the illegal code) and so on.	
ImageRecordsTamper-resistance	Video/Image with watermark tech and check function	
Certificaions		
CE	SECE1505159	
FCC	SEFV1505159	



Ultra Series | DHI-ITC302-RF1A-(IR)

Ordering Information			
Туре	Part Number		
3MP camera	DHI-ITC302-RF1A	Support white lamp	
	DHI-ITC302-RF1A-IR	Support IR lamp	

Accessories

Optional:





Bracket

Housing

Dimensions (mm/inch)

Lens







Rev 001.001 © 2016 Dahua. All rights reserved. Design and specifications are subject to change without notice.