

# DH-PFB2213C

Ceiling Mount Bracket



- · Built of aluminum alloy, it is cost-effective.
- · Elegantly designed, it has internal wiring and is compatible with the lightweight bullet camera.
- · It can be scaled from 800 to 1500 mm.







#### **System Overview**

Dahua Mounting Bracket works with front-end services, supporting installation methods such as wall mount, pole mount, corner mount and in-ceiling mount. Select brackets are designed to suit complex scenes, making them convenient to use in environments with high temperatures, humidity, frequent vibrations, and in locations that are highly corrosive. These highly reliable brackets are easy to install and use.

#### Scene

Ideal for mounting cameras, and works in temperatures ranging from  $-40\,^{\circ}\text{C}$  to  $+60\,^{\circ}\text{C}$  ( $-40\,^{\circ}\text{F}$  to  $+140\,^{\circ}\text{F}$ ) and in environments with a relative humidity of less than 90%.

#### **Technical Specification**

**Operating Temperature** 

#### Structure


| Casing Material      | Aluminum alloy                                                               |  |
|----------------------|------------------------------------------------------------------------------|--|
| Product Dimensions   | Φ100.0 mm × 800.0 mm-Φ100.0 mm × 1500.0 mm (Φ3.94" × 32.09"-Φ3.94" × 59.06") |  |
| Appearance Color     | White                                                                        |  |
| Net Weight           | 0.42 kg (0.93 lb)                                                            |  |
| Gross Weight         | 0.63 kg (1.39 lb)                                                            |  |
| Load Bearing         | 1.0 kg (2.20 lb)                                                             |  |
| Installation         | Ceiling mount                                                                |  |
| Screw Thread Type    | 1/4-20-UNC                                                                   |  |
| Applicable Model     | Please see "Camera Accessories Selection"                                    |  |
| Packaging Dimensions | 125.0 mm × 125.0 mm × 820.0 mm (4.92" × 4.92" × 32.28") (L × W × H)          |  |
| Environment          |                                                                              |  |

-40 °C to +60 °C (-40 °F to +140 °F)


| Operating Humidity   | < 90% (RH)                           |
|----------------------|--------------------------------------|
| Storage Temperature  | -40 °C to +60 °C (-40 °F to +140 °F) |
| Storage Humidity     | 10%-90% (RH)                         |
| Anti-corrosion Level | Basic Protection                     |

| Ordering Information |             |                       |
|----------------------|-------------|-----------------------|
| Туре                 | Model       | Description           |
| Camera<br>Mount      | DH-PFB2213C | Ceiling Mount Bracket |
|                      | PFB2213C    | Ceiling Mount Bracket |

#### Installation



## Dimensions (mm[inch])



### **Package Information**

- $\cdot$  Ceiling mount bracket  $\times$  1
- ST4×25 screws × 4
- Plastic expansion bolt × 4
- Mounting Sticker × 1