

ATS1110A-N

Advisor Advanced keypad 2x16 characters LCD

Remote arming stations

The ATS1110A is part of the Remote Arming Station family for the Advisor Advanced security system. The RAS family consists of a range of keypads and card readers which can be used in different environments, in and out-door. The ATS1110A can be used for configuration and management of the system, as well as for opening doors and arming/disarming areas. In an easy way, the ATS1110A gives a status overview from your security system with both visual and audio indicators.

Product overview

The ATS1110A is a modern ergonomic design and has a clearly readable text on a 2 x 16 characters LCD for displaying system programming, alarm and access control functions. The viewing angle of the display is adjustable via the keypad as well as the volume level of the built-in buzzer. Four arrow keys will navigate the user easily through the programming and operational features and 6 additional functions key will complete this user-friendly interface.

Indications

Four status LED's will continuously update the user on mains condition, faults, access control and alarms.

Green (Power), Yellow (Fault), Blue (Access) and Red (Alarm) are controlled by the control panel.

The Arming Station can display the status of 16 areas using 16 LED's on the front, while the LCD shows details of alarms or a pre-programmed text.

The area may be identified by viewing the 16 area LEDs visible when the RAS cover is open or removed and the indicates area is armed (on), area in fault (slow flash) and area alarm (fast flash)

Mounting

The RAS cover is hinged at the bottom. To open, grasp the cover at the sides or the top and pull gently - the cover will swing down on its pins. The cover may be fully removed by gently prising one of the pins away from the body of the RAS and pulling. The metal mounting plate at the rear is held by a locking screw.



Details

- 2 x 16 characters LCD
- User adjustable buzzer
- User adjustable LCD contrast
- 16 Area indication
- Door release indication

ATS1110A-N

Advisor Advanced keypad 2x16 characters LCD

Technical specifications

General

User interface	LCD de 2 x 16 caracteres, Botones Táctiles
Product line	Advisor Advanced
LED's de estado	16

Sistema

Teclas de Función	4
Tipo de Direccionamiento	Interruptores DIP
Tipo de cable soportado	WCAT 52/54 or equivalent

Comunicación

Tipo de comunicación	Cableado
----------------------	----------

Entradas/Salidas

Entradas	1
Tipo de entrada	Request to Exit
Salidas	1
Tipo de salida	Open collector, 50 mA Max

Eléctrico

Voltaje de funcionamiento	9 to 14 VDC
Consumo de corriente	26 mA typical 95 mA max

Físico

Dimensiones físicas	92 x 165 x 25,4 mm
Peso neto	296 gr
Color	Blanco
Form factor	Vertical
Cubierta	Cubierta abatible
Tipo de Montaje	Montaje en Superficie

Medioambiental

Temperatura de funcionamiento	0 to +50°C
Humedad relativa	95% noncondensing
Environment	Interior
Clasificación IP	IP30

Regulatory

Grado EN50131	Grado 3
Cumplimiento	CE, RoHS
Certification	VdS



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 16 May 2022 - 14:19