

FE290

Retenedor electromagnético de 400N para montaje en suelo con pulsador de desbloqueo.

General

The FE290 is a mains powered surface mount door holder, in a Bayblend housing, which offers a 400N holding force and a release button. Cable entry is possible from the back or from the sides, and the release button can be located at the top, or one of the sides.

Magnet construction

The magnet is constructed with a pressed coil and anti-remenance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

Housing

The plastic housing is manufactured from Bayblend and contains 30% PA6 glass fiber, which makes it much stronger than standard ABS. Bayblend offers high heat resistance, high impact and notched impact strength, and high stiffness and dimensional stability.

Installer friendly

- For practical ease of installation, the door holder comes complete with electrical screw terminals.
- The housing is predrilled in a practical, standard format for rapid mounting.
- The door holder is supplied complete with a keeper plate, which offer angular adjustment.
- The release button can be position in three different locations: top, left or right
- Cable entry can be done in four different locations: back, top, left or right.



Details

- Low power - 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- Release button
- Keeper plate included

FE290

Retenedor electromagnético de 400N para montaje en suelo con pulsador de desbloqueo.

Technical specifications

General

Fuerza de retención N (Newtons)	400
---------------------------------	-----

Botón de liberación	Si
---------------------	----

Diodo de supresión de chispa	Yes
------------------------------	-----

Protección contra inversion de polaridad	Yes
------------------------------------------	-----

Electrical

Tipo de fuente de alimentación	230 VAC
--------------------------------	---------

Consumo de corriente	1.6 W
----------------------	-------

Ciclo de trabajo	100%
------------------	------

Physical

Dimensiones físicas	85 x 110 x 38 mm (W x H x D)
---------------------	------------------------------

Environmental

Clasificación IP	IP54 (Magnet) IP42 (Connection)
------------------	------------------------------------



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 14 September 2022 - 11:12