

DHI-LM22-F200

Dahua 21.5 inch LED Monitor



Features :

- Suitable for continuous 24/7 operation
- 3 sides narrow bezel design, ultra-light base
- 178°/178° extra-wide viewing angle for overall viewing performance
- High fidelity digital processing for a brilliant and vivid video
- Support multiple signal inputs including HDMI and VGA
- Low energy consumption, long service life



Technical Specification

Display

Model	DHI-LM22-F200
Screen Size	21.5 inch
LCD Technology	VA
Aspect Ratio	16:9
Resolution	1920 (H) × 1080 (V)
Backlight	ELED
Brightness	250 cd/m ² (typ.)
Contrast Ratio	3000:1
Display Color	8 bit
Viewing Angle	178° (H) / 178° (V)
Response Time	OD 5 ms
Refresh Rate	100Hz
Lifespan	30,000 hrs

Device Ports

Input Port	1 × HDMI, 1 × VGA
Output Port	1 × Audio out

Power & Environmental Conditions

Power Supply	12 VDC, 2.5 A
--------------	---------------

Power Type	Power adapter
Power Consumption	15 W (basic), 15 W (typ.), 23 W (max)
Standby Power Consumption	<0.5 W
Operating Temperature	0 °C to +40 °C (+32 °F to +104 °F)
Operating Humidity	10%–85% (RH)
Storage Temperature	–20 °C to +55 °C (–4 °F to +131 °F)
Storage Humidity	10%–90% (RH)

General

Product Dimensions	492.2 mm × 378.4 mm × 170 mm (19.38" × 14.90" × 6.69") (W × H × D) with base
Package Size	550.00 mm × 370.00 mm × 120.00 mm (21.65" × 14.57" × 4.72") (W × H × D)
Frame Width	U/L/R: 1.1 mm/1.1 mm/1.1 mm, D: 16.8 mm
Net Weight	2.3 kg (5.07 lb)
Gross Weight	3.28 kg (7.23 lb)
Accessory	Power adapter, base, HDMI cable, user's manual (QR code), QSG, legal and regulatory information, etc.
Optional Accessory	Wall mount
Wall Mount VESA	100 mm × 100 mm (3.94" × 3.94")

Certifications

Certifications	CE EMC, CE LVD, CE ERP
----------------	------------------------

Dimensions (mm[inch])

