

NC-PX3E

Enhanced Conventional Fire and Extinguishing Panel - 3 Zone

Overview

The New Conventional fire control panels offer state of the art architecture in configurations that deliver an uncomplicated solution for small to mid-sized conventional applications. With their clean and attractive contemporary design, they fits with any decor. The basic and intuitive user interface with icons make easy their application everywhere.

With support for multiple lines of conventional detectors and accessories, these quick-to-configure systems offer versatility that benefits building owners and installation/maintenance companies alike.

The Panel

The NC-PX3E is a networkable, enhanced conventional fire alarm and extinguishing control panel. It is supplied in local language with 3 fire zones that support up to 32 devices per zone. These zones may be configured for extinguishing in single zone or double zone configuration in any combination of zones. In addition the panel offers supervised outputs for first stage notification, second stage notification as well as optical warning indicators and actuator activation. Standard relay outputs are provided for EN54 compliance and system status notification, as well as multiple inputs for system control.

Options

The panels support 2 types of auxiliary relay boards, one with 4 standard relays, and one with 4 supervised relays. With these boards the panel outputs may be expanded with up to 16 additional outputs.

The NC-PX3E supports class A (redundant ring) and B (standard bus) networking with up to 32 nodes including conventional and addressable panels and repeaters via an optional network interface. This allows full remote control and inputs to and from other nodes in the system, providing superior flexibility in system organisation and planning.

Approvals & Compliance

The product line carries the following accreditations:

- EN54:2, EN54:4 and CE approved
- CPR certified
- EN12094-1 certified

- WEEE compliant
- RoHS compliant



Detalles

- Modern, elegant design with basic and intuitive user interface with icons.
- Easy removable parts for quick and easy installation
- Normal & head-out supervision support per zone
- Three detection zones
- Single zone, double zone or any combination of zones configurable for release
- 6 Pre-configured relays and 8 supervised inputs for extinguishing control
- Configurable fire routing, sounder, extinguishing, reset and door monitoring delays
- Configurable "Hold Mode" type-A or type-B
- Sounders configurable for pulsing or continuous operation
- Extinguishing agent flow confirmation
- Continuous or resettable 24 VDC auxiliary supply
- Auxiliary standard & supervised relay output support
- Default support for special functions such as: - EN54 compliant user access levels - Basic & Advanced level configuration - mixed zones - front panel diagnostics with test & disable control - one-man walk test
- Redundant networking to 1X conventional and 2X addressable nodes
- Intrinsically safe and EN54-13 zone support

NC-PX3E

Enhanced Conventional Fire and Extinguishing Panel - 3 Zone

Especificaciones técnicas

General

Capacidad máxima del sistema (número de dispositivos)	hasta 1260
Tamaño de la red (nodos)	hasta 21

Eléctrico

Tipo de fuente de alimentación	VAC
Consumo de corriente	4 A @ 24 VDC
Voltaje de funcionamiento	110 VAC @ 50 Hz or 230 VAC @ 50 Hz (+10% -15%) Cablet type: 3 x 1.5 mm ² (live, neutral, earth)
Consumo de corriente	3.15 A @ 110/1.5 A @ 240 VAC 2.78 A (Alarm, no devices) 0.39 A (Quiescent, no devices)

Lazo

Capacidad máxima del lazo	3
---------------------------	---

Zona

Máxima capacidad de zona	hasta 3
Voltaje de funcionamiento	22 VDC (18 to 24 VDC)
Cantidad de dispositivos por lazo	20 max.
Calificación	65 mA (max. Load)
Ratio del cable	40 ohm (max. resistance), 500 NF (max. capacitance)

Batería en reposo

Capacidad	2 x 12 V, 12 Ah (SLA)
-----------	-----------------------

Físico

Factor de forma	Medio
Dimensiones físicas	440 x 480 x 140 mm (W x H x D)
Peso neto	3.9 kg (without battery)
Peso de envío	6 kg
Color	Gris (RAL 7035)
Tipo de Montaje	Montaje en Superficie
Entradas de cable	Ø 20 mm - 20 / 2 / 26 (top / bottom / rear)

Medioambiental

Temperatura de funcionamiento	-5 to +40°C
Temperatura de almacenamiento	-20 to +70°C
Humedad relativa	10 to 95% noncondensing
Entorno	Interior
Clasificación IP	IP30

Regulador

Cumplimiento	CPD, RoHS, WEEE
Certificación	EN12094-1, EN54-13, EN54-2, EN54-4

Supervised Input

	6
Use	MCP Start, MCP Hold, MCP Abort, Pressure Switch, Gas Flow, Door Monitor

Non Supervised Input

	2
Use	Auto/Manual mode, Remote Reset

Supervised Output

	4
Use	Fire Sounders, Extinguishing Sounders, Optical Indications, Actuator
Notification	2 x 500 mA @ 24 VDC
Visual indicators	1 x 500 mA @ 24 VDC
Actuator	1 x 1 A @ 24 VDC

Non Supervised Output

	4
Use	Hold Mode, Abort Mode, Manual Mode, Release Indication
Specification	6 x 2 A @ 30 V

Auxilliary Supply Output

Output voltage	24 VDC (21 to 28 VDC)
Load (max.)	250 mA



Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.