

PM844-A

Fuente de alimentación 12Vcc/4A en caja metálica.

High efficient switch mode 12 Volt dc Power Supply featuring Mains and Battery Monitoring with two independent volt free fault outputs. Full Rated Current to Load 4 Amp plus 0.5 Amp average for battery charging



Detalles

- Continuous full rated current to load
- Additional 0.5 A (average) to charge standby battery
- High efficiency electronics for reduced running costs and lower operating temperatures
- Modular construction for ease of maintenance and installation
- Full electronic short circuit and overload protection on load output under mains operation
- Lid opening tamper detection
- Increased room space for additional PCBs or cables
- Deep Discharge Protection
- 2 independent volt free fault outputs
- Reverse battery connection protection
- PSU fault indicator (Red LED)
- Battery Disconnected fault detection

PM844-A

Fuente de alimentación 12Vcc/4A en caja metálica.

Technical specifications

General

Fusible(s) 230 VAC input 3.15 A, 12/24 V output 4 A

Electrical

Entrada principal 100 to 240 VAC

Output

Voltaje de la salida de potencia 13,8 VCC

Ondulación de salida 150 mV pk-pk max.

Power output current mains 4 A

Battery

Máx. capacidad de la batería 18 Ah 12 V

Corriente de carga de la batería 0.5 A

Physical

Dimensiones físicas 355 x 330 x 80 mm (W x H x D)

Peso neto 4.30 kg (excluding battery)

Colour Blanco

Form factor Envolverte de acero

Environmental

Temperatura de funcionamiento -10° to +40° C

Temperatura de almacenamiento -20 to 80°C

Humedad relativa 95% noncondensing

Regulatory

Cumplimiento CE, REACH, RoHS 2, WEEE



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 5 May 2023 - 9:28