

# EU POWER SUPPLY, 9W



## TECHNICAL DATA

### GENERAL

|                                  |               |
|----------------------------------|---------------|
| Input voltage                    | 100 - 240 VAC |
| Input frequency                  | 50 / 60 Hz    |
| Input current                    | 0.6 A         |
| Output voltage                   | 0.5 A         |
| Output current                   | 1.0 A         |
| Input voltage absolute maximum   | 90 - 264 VAC  |
| Input frequency absolute maximum | 47 - 63 Hz    |
| Inrush current                   | 60 A          |

|                                   |                   |
|-----------------------------------|-------------------|
| Output voltage absolute maximum   | 8.55 - 9.45 VDC   |
| Short circuit protection          | ✓                 |
| HIPOT (dielectric withstand test) | 4242 VDC          |
| MTBF                              | 50000 h           |
| Input connector                   | EU (Type C)       |
| Output connector                  | 4-pin, 3 mm pitch |
| Operating temperature             | -10 ~ +40 °C      |
| Storage temperature               | -20 ~ +70 °C      |
| Weight                            | 94 g              |
| RoHS:                             | ✓                 |

Certification

**Safety:** IEC 62368-1: 2018  
**EMC:** EN 55032:2015+A11:2020, CISPR 32:2015, EN IEC 61000-3-2:2019, EN 61000-3-3:2013+A1:2019, EN 55035:2017+A11:2020, CISPR 35:2016

