

# Declaration of Performance No. 0359-CPR-00272 REV 06

Declaration of Performance according to the Construction Products Regulation EU No. 305/2011 and UKCA requirements

|   |  |
|---|--|
| 1. Unique identification code of the product type   | Model(s): SC-11-1200, SC-11-2200, SC-11-1201, SC-11-2201 and SC-61-0002 communication card (separate EN 54-21 approved)<br>Brand(s): SmartCell   |
| 2. Type, batch, or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4)   | Each individual product is identified with a label containing a unique serial number.  |
| 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer  | Fire detection and fire alarm systems – Control & Indicating Equipment - EN54-2<br><br>Fire detection and fire alarm systems – Power Supplies - EN54-4<br><br>Fire detection and fire alarm systems – Components using radio links EN54-25   |
| 4. Name, registered trade name, or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5)   | KGS Manufacturing Poland Spółka Z o. o.<br>ul. Kolejowa 24<br>39-100 Ropczyce, POLAND  |
| 5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2)  | EMS Limited<br>Technology House, Sea Street, Herne Bay, Kent, CT6 8JZ.   |
| 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V   | System 1   |
| 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard   | Intertek Deutschland GmbH– 0905; performed type testing and the initial inspection of the manufacturing plant and of the factory production control with continuous surveillance assessment and approval of the factory production control under system 1 and issued an EC certificate of conformity.<br>0905-CPR-00272<br><br>Intertek UK – 0359 performed type testing and initial inspection of the manufacturing plant and of the factory production control with continuous surveillance assessment and approval of the factory production control under system 1 and issued an EC certificate of conformity. |
| 8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:   | Not applicable, see point 7  |
| 9. Declared performance: All requirements including all Essential Characteristics and the corresponding performances for the intended use or uses indicated in point 3 above have been determined as described in the harmonised technical specifications: EN54-18:2005 and EN 54-25: 2008 mentioned in the table(s) below. |  |

## Fire detection and fire alarm systems – Control & Indicating Equipment - EN54-2

| Essential characteristics  | Performance | Requirement clauses in this European standard |
|--|-------------|---|
| Performance under fire conditions  | PASS        | 4, 5, 7 (notes a,b)                           |
| Response delay (response time)   | PASS        | 7.1, 7.7, 7.11, 7.12 (note a)                 |
| Operational reliability  | PASS        | 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14 (note a) |
| Durability of operational reliability, Temperature resistance  | PASS        | 15.4  |
| Durability of operational reliability, Vibration resistance  | PASS        | 15.6, 15.7, 15.15                             |
| Durability of operational reliability, Electrical resistance   | PASS        | 15.8 to 15.13                                 |
| Durability of operational reliability, Humidity stability  | PASS        | 15.5, 15.14                                   |
| a) For compliance with this standard it is not necessary to provide the optional functions specified in the standard. However, if a manufacturer chooses to include any of these options in the equipment, then the associated requirements shall be met and have to be included in type testing and certification (see Clause 4 of this standard).<br>b) The products covered by this standard are assumed to function during the alarm condition, in an event of fire, before the fire becomes so large as to affect their functioning. There is therefore no requirement to function when exposed to direct attack from fire. |             |   |

**Fire detection and fire alarm systems – Power Supplies - EN54-4**


| Essential characteristics   | Performance | Requirement clauses in this European standard |
|---|-------------|---|
| Performance of power supply   | PASS        | 4, 5, 6 (notes a)                             |
| Operational reliability   | PASS        | 4, 5, 6, 7, 8 (note a)                        |
| Durability of operational reliability,<br>Temperature resistance  | PASS        | 9.5   |
| Durability of operational reliability,<br>Vibration resistance  | PASS        | 9.7, 9.8, 9.15                                |
| Durability of operational reliability,<br>Electrical resistance   | PASS        | 9.9 to 9.13                                   |
| Durability of operational reliability,<br>Humidity stability  | PASS        | 9.6, 9.14                                     |
| a) The products covered by this standard are assumed to function during the alarm condition, in an event of fire, before the fire becomes so large as to affect their functioning. There is therefore no requirement to function when exposed to direct attack from |             |   |

**Fire detection and fire alarm systems – Components using radio links EN54-25**

| Essential characteristics   | Performance | Requirement clauses in this European standard  |
|---|-------------|--|
| Performance parameters under fire conditions  | PASS        | 4.1, 4.2.2, 5.2, 8.3.7 (see note a)  |
| Response delay (response time to fire)  | PASS        | 8.2.3, 8.2.6 (see note a)  |
| Operational reliability   | PASS        | 4.2.1, 4.2.3 to 4.2.7, 5.3, 5.4, 6, 7, 8.2.2, 8.2.4, 8.2.5, 8.2.7, 8.2.8 <sup>b</sup> , 8.2.9, 8.3.1, 8.3.2, 8.3.3, 8.3.5, 8.3.6 |
| Durability of operational reliability,<br>Temperature resistance  | PASS        | 8.3.9 <sup>c</sup> , 8.3.10 <sup>c</sup> , 8.3.11  |
| Durability of operational reliability,<br>Vibration resistance  | PASS        | 8.3.16 <sup>c</sup> , 8.3.17 to 8.3.19   |
| Durability of operational reliability,<br>Humidity resistance   | PASS        | 8.3.12 <sup>d</sup> , 8.3.13 <sup>e</sup> , 8.3.14   |
| Durability of operational reliability,<br>Corrosion resistance  | PASS        | 8.3.15 <sup>c</sup>  |
| Durability of operational reliability,<br>Electrical stability  | PASS        | 8.3.20   |
| <p>a The products covered by this standard are assumed to enter the alarm condition, in an event of fire, before the fire becomes so large as to affect their functioning. There is no requirement to function when exposed to direct attack from fire.</p> <p>b Only applicable to components required to indicate loss of communication or to transmit this information to the CIE.</p> <p>c Not applicable for CIE.</p> <p>d Not applicable for CIE and smoke detectors.</p> <p>e Only applicable for CIE and smoke detectors.</p> |             |  |


10. The performance of the product identified in items 1 and 2 is in conformity with the declared performance in point 9.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.


Signed by: Daniel Griffin  
Director of Product & Compliance



Location: EMS Limited,  
Technology House, Sea Street,  
Herne Bay, Kent, CT6 8JZ, U.K.

Date: 26<sup>th</sup> March 2025

| Regulation (EU) No. 305/2011 CPR Supplementary CE marking information  |
|--|
|                                     |
| Identification of the Certification Body: 0905   |
| Manufacturer: KGS Manufacturing Poland Spółka Z o. o, ul. Kolejowa 24, 39-100 Ropczyce, POLAND                       |
| Last two digits of year CE mark was first placed: 19   |
| Declaration of Performance (DoP) Number: 0359-CPR-00272 REV 06   |
| EN54-2:1997+A1:2006, EN 54-4:1998+A1,A2, and EN 54-25:2008   |
| Unique identification of product type: See the product label for the product documentation part number and revision. |
| Intended use: See DoP point 3.   |
| Essential characteristics: See DoP point 9.  |

| UKCA marking information   |
|--|
|                                     |
| Identification of the Certification Body: 0359   |
| Manufacturer: KGS Manufacturing Poland Spółka Z o. o, ul. Kolejowa 24, 39-100 Ropczyce, POLAND                       |
| Last two digits of year UKCA mark was first placed: 25   |
| Declaration of Performance (DoP) Number: 0359-CPR-00272 REV 06   |
| EN54-2:1997+A1:2006, EN 54-4:1998+A1,A2, and EN 54-25:2008   |
| Unique identification of product type: See the product label for the product documentation part number and revision. |
| Intended use: See DoP point 3.   |
| Essential characteristics: See DoP point 9.  |